MATERIAL SAFETY DATA SHEET

1、 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name： XS-T90
Use： Photopolymer for Stereolithographic Apparatus with DLP
Company： Jiangmen Xingsheng Precision Manufacturing Co., Ltd.
Tel： 17028327148
Email： 1050619592@qq.com
Website： www.xmicro3d.com
Address： No. 40 Jinzhou Road, Huicheng, Xinhui District, Jiangmen City, Guangdong Province,China

2、 HAZARDS IDENTIFICATION

2.2 Label elements

Labeling according Regulation (EC) No 1272/2008

Pictogram

Signal word Attention

Hazard statements H315

Cause skin irritation H317

May cause an allergic skin reaction H319

Cause serious eye irritation H335

May cause respiratory irritation H411

Toxic to aquatic life with long lasting effects

Precautionary statements P273

Avoid release to the environment P280

Wear eye protection/face protection P280

Wear protective gloves P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Supplemental Hazard Statements none

2.3Other hazards-none

3、 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

Mixture of acrylic oligomers and epoxy resin

Hazardous components

Hazardous Components	CAS NO.	Concentration(wt%)	Hazardous Substance
(Meth)acrylate monomer	Confidential	10–40%	NO
(Meth)acrylate oligomer	Confidential	40–85%	NO
Photoinitiator	Confidential	0.2–5%	NO

4、 FIRST AID MEASURES

Inhalation: Move to fresh air.Call a physician immediately.

Eye contact: Rinse immediately with plenty of water for at least 15 minutes.If eye irritation persists, consult a specialist.

Skin contact: Wash off immediately with soap and plenty of water.If skin irritation persists, call a physician.

Ingestion: Immediately give plenty of water (if possible charcoal slurry).Do not induce vomiting.Obtain medical attention.

5、 FIRE-FIGHTING MEASURES

Suitable extinguishing media：Water spray，Carbon dioxide (CO_2)，Foam，Dry powder.

Extinguishing media whichmust not be used for safety reasons： High volume water jet.

Special protectiveequipment for fire-fighters ： Wear self-contained breathing apparatus and protective suit.

Further information： Burning produces obnoxious and toxic fumes，Carbon oxides.

6、 ACCIDENTAL RELEASE MEASURES

Environmental precautions ：Do not allow material to contaminate ground water system.Prevent product from entering drains.

Methods for cleaning up：Sweep up and shovel into suitable containers for disposal.

7、 HANDLING AND STORAGE

Handling

Advice on safe handling：Provide sufficient air exchange and/or exhaust in work rooms.

Ensure adequate ventilation.

Handle and open container with care.

Storage

Further information on storage conditions：Keep away from food, drink and animal feeding stuffs.

Keep container tightly closed.
Keep at temperatures between 25 and 35 °C.

8、EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters
Components: None Established
Personal protective equipment
Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment.Filter type AX-P2 (organic vapours, particles)
Eye protection: Tightly fitting safety goggles.Face-shield.
Hand protection: Material of gloves for long term application (BTT>480 min): Butyl rubber
Ethyl Vinyl Alcohol Laminate (EVAL)
Material of gloves for short term/splash application: Nitrile rubber Neoprene rubber
Use gloves approved to relevant standards.
Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material and dexterity. Always seek advice from glove suppliers.

Skin and body protection: Protective suit.Safety shoes.
Protective measures: Keep away from sources of ignition - No smoking.
Avoid contact with skin, eyes and clothing.

9、 PHYSICAL AND CHEMICAL PROPERTIES

Form Black Liquid
Odour Slight
Thermal decomposition > 240 °C
Flash point > 95 °C
Method:PMCC
Vapour pressure < 100 Pa at 25 °C
Density 1.05/cm3 at 30 °C
Water solubilityat 20 °C
Note: practically insoluble
Miscibility with water
Immiscible at 20 °C
Viscosity, dynamic
100cps at 25 °C
PH Value 3-6

10、 STABLITY AND REACTIVITY

Conditions to avoid

Note: Take necessary action to avoid static electricity discharge.

Materials to avoid

Strong acids and strong bases.

Strong oxidizing agents.

Hazardous decomposition products

Carbon oxides. Burning produces obnoxious and toxic fumes

11、 TOXICOLOGICAL INFORMATION

Acute oral toxicity LD50 rat

Dose > 2,000 mg/kg

Eye irritation Moderate eye irritation rabbit

Skin irritation Moderate skin irritation rabbit dermal

Sensitization Causes sensitization. guinea pig dermal

12、 ECOLOGICAL INFORMATION

Elimination information (persistence and degradability)

Biodegradability

Result: Not readily biodegradable.

Ecotoxicity effects

Further information on ecology

Additional ecological information

Avoid subsoil penetration.

Prevent product from entering drains.

Do not contaminate surface water.

13、 DISPOSAL CONSIDERATIONS

Product: Must be incinerated, when in compliance with local regulations.

Container: Empty containers can be landfilled after cleaning.

Contaminated packaging None Established

14、 TRANSPORT INFORMATION

Land transport

ADR: Regulation: Not dangerous goods

RID: Regulation: Not dangerous goods

Sea transport

IMDG: Regulation: Not dangerous goods

Air transport

IATA-DGR: Regulation: Not dangerous goods

15、 REGULATORY INFORMATION

Labelling according to EEC Directive

Labelling required

Symbol(s) Xi Irritant

R-phrase(s)

R43May cause sensitization by skin contact.
R52/53Harmful to aquatic organisms, may cause long-term adverse effects in the aquaticenvironment. **S-phrase(s)**
S28After contact with skin, wash immediately with plenty of soap and water.
S37/39Wear suitable gloves and eye/face protection.
S61Avoid release to the environment. Refer to special instructions/safety data sheets.
Exceptionallabelingofspecial preparations Contains epoxy constituents. See information supplied by the manufacturer
Hazardous components whichmust be listed on the label Na
National legislation
Water contaminating class
2 water endangering
Notification status : EINECS yes
The formulation contains ELINCS substances. :
TSCA yes :
DSL yes :
AICS: no :
KECI (KR): no :
ENCS (JP): no

16、 OTHER INFORMATION

MSDS Creation Date 2025/09/09
MSDS Revision A
All information is based on results gained from experience and tests and is believed to be accurate but is given without acceptance of liability for loss or damage attributable to reliance thereon as conditions of use lie outside our control. Users should always carry out sufficient tests to establish the suitability of any products for their intended applications. No statements shall be incorporated in any contract unless expressly agreed in writing nor construed as recommending the use of any product in conflict of any patent.